

# PROCAT™ SE

## COMMERCIAL ZERO-TURN MOWERS

### BOB-CAT OFFERS THE TOTAL PACKAGE FOR PRODUCTIVITY

When you value everyday productivity, put ProCat value and performance on your crew. We've redesigned it with some of the ride comfort and ergonomic features as the Predator-Pro to deliver a great cut with less operator fatigue. You'll also cut downtime, thanks to ProCat reliability and easy-access maintenance. In other words, it's the total package.

Shown with optional folding ROPS.



## IMPROVED VISIBILITY AND STABILITY

- /// Less slip, more grip on hills and slopes
- /// Seat platform now 2" lower to enhance center of gravity
- /// Frame redesigned for better operator visibility, closer trimming without collateral damage to landscaping, trees and buildings
- /// New control levers eliminate lost linkage motion for smoother operation, less wheel marking and spin



[bobcatturf.com](http://bobcatturf.com)

		ProCat SE KOH CV680 52 SD	ProCat SE KOH CV740 61 SD	ProCat SE KAW FX651V 52 SD	ProCat SE KAW FX730V 61 SD
	Model	942520H	942521H	942522H	942523H
<b>Engine</b>	Make	Kohler Command Pro CV680	Kohler Command Pro CV740	Kawasaki FX651V	Kawasaki FX730V
	Engine Displacement*	674cc (41.1 cu. in.)	725cc (44 cu. in.)	726 cc [44.3 cu. in.]	726 cc [44.3 cu. in.]
	Lubrication	Full pressure - spin-on filter			
	Air Filtration System	Dual stage heavy-duty canister air filter			
<b>Deck</b>	Deck Size	52"	61"	52"	61"
	Blade Tip Speed	18,404 fpm @ 3600 engine rpm	18,854 fpm @ 3500 engine rpm	18,404 fpm @ 3600 engine rpm	18,854 fpm @ 3500 engine rpm
	Deck Design	DuraDeck™ side discharge w/ molded rubber chute - Fabricated dual layer 10-gauge top			
	Deck Skirts	7-gauge skirts and baffles with adjustable anti-scalp rollers front and rear			
	Deck Lift Type	Manual foot lift with spring assist / RH or LH quick lift foot pedal			
	Spindle Type	Maintenance free w/1" shaft			
	Spindle Bearings	Double-sealed, precision ground ball bearings			
	Cutting Height	1" - 5.5"			
	Deck Drive	Warner Mag Stop 225 ft. lb. electric clutch			
<b>Drive</b>	Transmission	Hydro-Gear variable displacement pumps; hydraulic oil cooler; parker wheel motors			
	Pump Size	12cc			
	Ground Speed	11.5 mph			
	Seat	Premium high back with extra thick foam and elastomeric sling for a smooth ride - Fore and aft adjusters - Quick adjust armrests			
<b>Tires</b>	Rear Tires	23 x 10.50-12 4-ply	24 x 12.00-12 4-ply	23 x 10.00-12 4-ply	24 x 12.00-12 4-ply
	Front Tires	13 x 6.50-5 Pneumatic caster wheels	13 x 6.50-5 Pneumatic caster wheels	13 x 6.50-5 Pneumatic caster wheels	13 x 6.50-5 Pneumatic caster wheels
	Parking Brake	Drum breaks			
<b>Fuel</b>	Fuel Capacity	14 Gallons			
	Hour Meter	Digital hour meter with service minder for engine oil and filter, engine air filter and and hydraulic oil and filter			
<b>Size</b>	Height	49"			
	Length	82"			
	Weight/Wet	1,256 lbs	1,293 lbs	1,256 lbs	1,293 lbs

\* Power ratings are provided by the engine manufacturer. Actual power output is dependent upon many factors including engine rpm, air density and engine conditions. For further information, contact Technical Service at Schiller Grounds Care, Inc at 877-596-6337.

Specifications while correct at the time of printing may change without notice.  
BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.  
© 2012 Schiller Grounds Care, Inc. All Rights Reserved.  
One BOB-CAT Lane, Johnson Creek, WI 53038  
www.bobcatturf.com • 920-699-2000

**Your Local Dealer is**