



Exactly What You Need™

Larger fuel tanks
for higher
productivity

Standard 4-Point
Full Suspension Seat



Heavy-gauge deck
for durability

Maintenance-free
spindles and caster
wheel bearings

Adjustable cutting height
from 1-1/2 to 5 inches
in 1/4 inch increments

Choice of 61-
or 72-inch deck

Anti-scalp rollers for
superior contour mowing

PREDATOR-PRO™

**Our Premium Professional
Predator-Pro Zero Turn Mower
offers rugged features and
exceptional options to deliver a
superior cut for all your turf needs.**

- Ergonomically designed, easy-access operator controls to reduce fatigue
- Lifetime Warranty on Deck, Deck Cradle & Engine Deck
- Adjustable dampeners let YOU configure the level of dampening
- Versa-FLO adjustable deck opening for cutting in all grasses and conditions
- Extreme Discharge System for superior clipping dispersal.
- On-the-fly adjustable tracking controls
- Quick Lift foot pedal to raise and lower deck on the go with ease

**The look of pure power.
An exciting, all-new zero-turn riding mower.**

www.bobcatturf.com • 1-866-469-1242

BOB-CAT® Predator-Pro

POWER

Model	Generac® V-Twin, Overhead Valve, Gas
Horsepower* (@ 3,600 rpm).....	Air Cooled, 33 (24.6 kW)
Ignition	Electronic, Electric Start
Model	Kawasaki® FX 1000DFI V-Twin, V-Valve with 3 Valves per cylinder, gas
Horsepower* (@ 3,600 rpm).....	Air Cooled, Digital Fuel Injection with Electronic Governor, 37 (24.6 kW)
Ignition	Electronic, Electric Start

VEHICLE

Fuel Capacity.....	12 gal. (45.4 L)
Transmission.....	Hydrostatic Drive with Dual Variable Displacement Pumps; Wheel Motors
Drive.....	Belt from Engine to Hydrostat Input Shafts; Hydrostatic Drive to Wheels
Hydraulic Capacity.....	0.65 gal. (2.5 L) Capacity; Oil Cooler
Brakes	Hydrostat Provides Dynamic Braking; Disc-Type Parking Brake
Steering	Lever-Type Steering Controls Independent Power to Each Wheel for Moving, Stopping and Turning
Seat.....	High-Back, Vinyl-Covered, Foam-Padded Full Suspension Seat with Adjustable Armrests, Fore/Aft Adjustment; Operator Weight Adjustment
Gauges and Controls	Hourmeter; Neutral Safety Switches; Throttle; Choke; Key Switch;
PTO.....	Clutch Switch; Steering and Traction Control Arms; Parking Brake Lever, Deck Lift Assist Foot Pedal

SPEED

16 cc Pumps

37-HP*	0 – 12.5 mph (20.1 km/h) Forward; 0 – 4 mph (6.4 km/h) Reverse
33-HP*	0 – 13.5 mph (21.1 km/h) Forward; 0 – 4 mph (6.4 km/h) Reverse
Turning Radius	True Zero-Turning Radius
Frame	7-Gauge Formed and Welded Steel

CUTTING DECKS

Cutting Width and Type.....	52" (1.32-m), 61" (1.55-m) or 72" (1.83-m) Side-Discharge
Deck Construction.....	Formed and Welded 10-Gauge Steel with 7-Gauge Reinforcements and Side Skirts, with Reinforced Leading Edge
Spindles	Large Top-Mounted, 1 (25-mm) dia. Shaft on Maintenance-Free Ball Bearings
Drive	Belt from Engine to Center Spindle; Reinforced V-Belt on Split Steel Pulleys (48 Deck) or Split Steel Pulleys (52" and 61" Decks) from Center Spindle to Outboard Spindles; 5.5 (140-mm) Idler

TIRES

61" Deck.....	(2) 24 x 12-12 4-Ply Turf Tread Drive Wheels
72" Deck.....	(2) 24 x 12-12 4-Ply Turf Tread Drive Wheels

Antiscalp Rollers

61" Decks.....	(7) 5 (127 mm): (2) Front Center, Left and Right Front, Left and Right Rear, Center Rear
72" Decks	(4) 5 (127 mm): Left and Right Front and Rear; (2) 4 (102 mm): Front and Rear Center

PRODUCTIVITY RATE / 8 HOURS

61" Deck	Up to 35.52 Acres (14.37 ha) at 9 mph (14.48 km/h)
72" Deck	Up to 41.92 Acres (16.96 ha) at 9 mph (14.48 km/h)
Height of Cut	1.5" to 5" (38 mm to 114 mm) in 0.25" (6.4 mm) Increments

Blades (3)

61" Deck.....	.21" (53 cm); .25" (6.4 mm) Thick
72" Deck.....	.24.5" (62.2 cm); .25" (6.4 mm) Thick

DIMENSIONS

Length.....80 (2.03 m)

Width

61" Deck.....	72" (1.83 m) Side-Discharge; 73" (1.9 m) with Chute Down; 62" (1.6 m) with Chute Up
72" Deck	84" (2.13 m) with Chute Down; 72" (1.83 m) with Chute Up
Overall Height	46.5" (1.2 m)

OPTIONS

Fold Down ROPS, 2-Post with Seat Belts, Tire – Knobby
23 x 10.50 – 12 (2 required), ZT200 48, 52/54 or 61 Deck Striping Kit,
48, 54 or 61 Mulch Baffle Kit, Kit – 61 Widetrack (widens track on
61 units), Kit – Mulching 51/52 or 61 Deck, Kit – ECO Plate 32 – 54 or
61, Kit – Front Adjust Lift Shaft for Electric Lift Kit (needed for older
machines without 4 point Adjustable Levelers), BOSS-Vac™ PRO 3
Bag Spindle Driven Collection System

Your Local Dealer Is:

Specifications while correct at the time of printing may change without notice.

BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.

© 2009 Schiller Grounds Care, Inc. All Rights Reserved.

One BOB-CAT Lane, Johnson Creek, WI 53038

www.bobcatturf.com • 920-699-2000

*The power ratings are provided by the engine manufacturer. Actual power output is dependent on many factors including engine rpm, air density, and engine condition. For further information on engine horsepower, please contact Schiller Grounds Care customer service at 877-596-6337.