



BOB-CAT[®]
Exactly What You Need[™]

PROCAT

The 2010 ProCat brings some **NEW** features that are sure to give you more comfort and performance.



- **Larger control levers and thicker grips add to the smooth operation and control**
- **Versa-FLO adjustable deck opening you can cut in all grasses and conditions**
- **On-the-fly tracking adjusters helps you keep your machine running as straight as a string**
- **Warranty Choice – 2 Year/2000 hours or 5 year/500 hours**



www.bobcatturf.com • 1-866-469-1242

BOB-CAT® PROCAT ZERO-TURN

POWER

Model

Engine.....Kawasaki® V-Twin, Overhead Valve, Gas
Horsepower* (@ 3,600 rpm).....Liquid Cooled, 26 (19.4 kW)
Ignition.....Electronic, Electric Start

Model

EngineKawasaki® FX Series V-Twin, Overhead Valve, Gas
Horsepower* (@ 3,600 rpm)22 (16.4 kW)
Ignition.....Electronic, Electric Start
Air FilterHeavy-Duty Canister Style

Model

EngineKawasaki® FX Series V-Twin, Overhead Valve, Gas
Horsepower* (@ 3,600 rpm)26 (19.4 kW)
Ignition.....Electronic, Electric Start
Air FilterHeavy-Duty Canister Style

Model

EngineKohler® Command Pro V-Twin, OHV
Horsepower* (@ 3,600 rpm)27 (19.4 kW)
Ignition.....Electronic, Electric Start
Air FilterHeavy-Duty Canister Style

Model

EngineKawasaki® FX Series V-Twin, Overhead Valve, Gas
Horsepower* (@ 3,600 rpm)29 (21.6 kW)
Ignition.....Electronic, Electric Start
Air FilterHeavy-Duty Canister Style

VEHICLE

Fuel Capacity12 gal. (36 l)
TransmissionHydrostatic Drive with Dual
Variable Displacement Pumps; Wheel Motors
DriveBelt from Engine to Hydrost at Input Shafts;
Hydrostatic Drive to Wheels
Hydraulic Capacity0.65 gal (25 l) Capacity; Oil Cooler
BrakesHydro Provides Dynamic Braking;
Disc-Type Parking Brake
SteeringLever-Type Steering Controls Independent Power
to Each Wheel for Moving, Stopping and Turning
SeatHigh-Back, Vinyl-Covered, Foam-Padded
Suspension Seat with Armrests, Fore/Aft Adjustment;
Operator Weight Adjustment
Gauges and ControlsHourmeter; Neutral Safety Switches;
Throttle; Choke; Key Switch; PTO Clutch
Switch; Steering and Traction Control Arms;
Parking Brake Lever
Speed0 – 18.5 mph (11.5 km/h) Forward;
0 – 4 mph (6.4 km/h) Reverse
Turning RadiusTrue Zero-Turning Radius
FrameFormed and Welded Steel Frame Rails

CUTTING DECKS

DuraDeck™ Construction with Versa-FLO adjustable deck opening

52", 61" DuraDecks Double Plated, 10-Gauge Steel Formed and
Welded, Reinforced Leading Edge with
7-Gauge Reinforcements and Side Skirts
SpindlesLarge Top-Mounted, 1" (25 mm) dia. Shaft
on Maintenance-Free Ball Bearings
DriveBelt from Engine to Center Spindle;
Reinforced V-Belt on Split Steel Pulleys
from Center Spindle to Outboard Spindles,
5.5" (140 mm) Idler with Replaceable Idler Arm Bolt

TIRES

Front:

52"(2) 13 x 5.00-6, 4-Ply Rated, Tubeless
61"(2) 13 x 6.50-5, 4-Ply Rated, Tubeless

Rear:

PROCAT

52.5" Deck(2) 23 x 10.50-12, 4-Ply Rated, Tubeless
61" Deck(2) 24 x 12.00-12, 4-Ply Rated, Tubeless

Antiscalp Rollers

52.5" Decks(6) 5" (127 mm), Front and Rear Center,
Left and Right Front, Left and Right Rear
61" Decks(8 total) 5" (127 mm), (2) Front Center, Left and
Right Front, Left and Right Rear, (2) Center Rear

PRODUCTIVITY RATE / 8 HOURS

52.5" DeckUp to 27.1 Acres at 8 mph (12.8 km/h)
61" DeckUp to 31.5 Acres at 8 mph (12.8 km/h)
Height of Cut1.5" to 5" (38 mm to 127 mm)
in .25" (64 mm) Increments

Blades (3)

52.5" Deck18" (46 cm); .205" (5.2 mm) Thick
61" Deck21" (53 cm); .25" (6.4 mm) Thick

DIMENSIONS

Length80" (2.03 m)

Width

52.5" Deck64.5" (1.6 m) with Chute Down;
58.25" (1.4 m) with Chute Up
61" Deck73" (1.9 m) with Chute Down;
62" (1.6 m) with Chute Up
Overall Height4.65" (1.2 m)

OPTIONS

2-Post Folding Rollover Protection Structure (ROPS) with Seat Belt;
Tire – Knobby 23 x 10.50 – 12 (2 required); ZT200 48", 52"/54" or 61"
Deck Striping Kit; 48", 54" or 61" Mulch Baffle Kit; Kit – 61" Widetrack
(widens track on 61" units); Kit – Mulching 51"/52" or 61" Deck;
Kit – ECO Plate 32" – 54" or 61"; Kit – Suspension Seat ZT200; Electric
Deck Lift Kit ZT200; ZT Hitch Kit; BOSS- Vac PRO™ Collection System

Your Local Dealer Is:

Specifications while correct at the time of printing may change without notice.
BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.
© 2010 Schiller Grounds Care, Inc. All Rights Reserved.
One BOB-CAT Lane, Johnson Creek, WI 53038
www.bobcatturf.com • 920-699-2000

*The power ratings are provided by the engine manufacturer. Actual power output is dependent on many factors including engine rpm, air density, and engine condition. For further information on engine horsepower, please contact Schiller Grounds Care customer service at 877-596-6337.