



**Exactly What You Need™**

# PROCAT

The 2009 ProCat brings some **NEW** features that are sure to give you more comfort and performance.



- **NEW** larger control levers and thicker grips add to the smooth operation and control
- **NEW** Versa-FLO adjustable deck opening you can cut in all grasses and conditions\*
- **NEW** on-the-fly tracking adjusters helps you keep your machine running as straight as a string\*
- **Warranty Choice** – 2 Year/2000 hours or 5 year/500 hours



\*Optional on DX models.

[www.bobcatturf.com](http://www.bobcatturf.com) • 1-866-469-1242

# SPECIFICATIONS

## BOB-CAT® PROCAT ZERO-TURN

### POWER

#### PROCAT DX

Engine .....Kawasaki® KAI V-Twin, Overhead Valve, Gas  
Horsepower (@ 3,600 rpm) .....19 (14.2 kW)  
Ignition .....Electronic, Electric Start  
Air Filter .....Ducted Dual Element Filter

#### PROCAT DX

Engine .....Briggs & Stratton® ELS, Overhead Valve Gas  
Horsepower (@ 3,600 rpm) .....26  
Ignition .....Electronic, Electric Start  
Air Filter .....Automotive Cartridge Type

#### PROCAT

Engine .....Kawasaki® V-Twin, Overhead Valve, Gas  
Horsepower (@ 3,600 rpm) .....21 (15.7 kW)  
Ignition .....Electronic, Electric Start  
Air Filter .....Heavy-Duty Canister Style

#### PROCAT

Engine .....Kohler® Command Pro V-Twin, OHV  
Horsepower (@ 3,600 rpm) .....27 (19.4 kW)  
Ignition .....Electronic, Electric Start  
Air Filter .....Heavy-Duty Canister Style

#### PROCAT

Engine .....Kawasaki® V-Twin, Overhead Valve, Gas  
Horsepower (@ 3,600 rpm) .....25 (19 kW)  
Ignition .....Electronic, Electric Start  
Air Filter .....Heavy-Duty Canister Style

#### PROCAT

Engine .....Kawasaki® FX Series V-Twin, Overhead Valve, Gas  
Horsepower (@ 3,600 rpm) .....27 (20.1 kW)  
Ignition .....Electronic, Electric Start  
Air Filter .....Heavy-Duty Canister Style

### VEHICLE

Fuel Capacity .....12 gal. (36 l)  
Transmission .....Hydrostatic Drive with Dual Variable Displacement Pumps; Wheel Motors  
Drive .....Belt from Engine to Hydrostat Input Shafts; Hydrostatic Drive to Wheels  
Hydraulic Capacity .....0.65 gal (2.5 l) Capacity; Oil Cooler  
Brakes .....Hydro Provides Dynamic Braking; Disc-Type Parking Brake  
Steering .....Lever-Type Steering Controls Independent Power  
to Each Wheel for Moving, Stopping and Turning  
Seat .....High-Back, Vinyl-Covered, Foam-Padded Suspension Seat  
with Armrests, Fore/Aft Adjustment; Operator Weight Adjustment  
Fuel Capacity .....12 gal. (36 l)  
Gauges and Controls .....Hourmeter; Neutral Safety Switches; Throttle; Choke; Key Switch;  
PTO Clutch Switch; Steering and Traction Control Arms; Parking Brake Lever  
Speed .....0 – 12 mph (13 km/h) Forward; 0 – 6 mph (64 km/h) Reverse  
Turning Radius .....True Zero-Turning Radius  
Frame .....Formed and Welded Steel Frame Rails

### CUTTING DECKS

#### DuraDeck™ Construction with Versa-FLO adjustable deck opening

52", 61" DuraDecks .....Double Plated, 10-Gauge Steel Formed and Welded,  
Reinforced Leading Edge with 7-Gauge Reinforcements and Side Skirts  
Spindles .....Large Top-Mounted, 1" (25 mm) dia. Shaft on Maintenance-Free Ball Bearings  
Drive .....Belt from Engine to Center Spindle; Reinforced V-Belt on  
Split Steel Pulleys from Center Spindle to Outboard Spindles,  
5.5" (140 mm) Idler with Replaceable Idler Arm Bolt

### TIRES

#### Front:

52" .....(2) 13 x 5.00 x 6, 4-Ply Rated, Tubeless  
61" .....(2) 13 x 6.50 x 5, 4-Ply Rated, Tubeless

#### PROCAT DX Rear:

52.5" Deck: .....(2) 23 x 8.50 x 12, 4-Ply Rated, Tubeless  
61" Deck: .....(2) 23 x 10.50 x 12, 4-Ply Rated, Tubeless

#### PROCAT Rear:

52.5" Deck: .....(2) 23 x 10.50 x 12, 4-Ply Rated, Tubeless  
61" Deck: .....(2) 24 x 12.00 x 12, 4-Ply Rated, Tubeless

#### Antiscalp Rollers

52.5" Decks .....(6) 5" (127 mm), Front and Rear Center,  
Left and Right Front, Left and Right Rear  
61" Decks .....(8 total) 5" (127 mm), (2) Front Center, Left and Right Front,  
Left and Right Rear, (2) Center Rear

### PRODUCTIVITY RATE / 8 HOURS

52.5" Deck .....Up to 27.1 Acres at 8 mph (12.8 km/h)  
61" Deck .....Up to 31.5 Acres at 8 mph (12.8 km/h)  
Height of Cut .....1.5" to 5" (38 mm to 127 mm) in .25" (64 mm) Increments

#### Blades (3)

52.5" Deck .....18" (46 cm); .205" (5.2 mm) Thick  
61" Deck .....21" (53 cm); .25" (6.4 mm) Thick

### DIMENSIONS

Length .....80" (2.03 m)

#### Width

52.5" Deck .....64.5" (1.6 m) with Chute Down; 58 .25" (1.4 m) with Chute Up  
61" Deck .....73" (1.9 m) with Chute Down; 62" (1.6 m) with Chute Up  
Overall Height .....46.5" (1.2 m)

### OPTIONS

2-Post Folding Rollover Protection Structure (ROPS) with Seat Belt; Tire – Knobby 23 x 10.50 – 12 (2 required); ZT200 48", 52"/54" or 61" Deck Striping Kit; 48", 54" or 61" Mulch Baffle Kit; Kit – 61" Widetrack (widens track on 61" units); Kit – Mulching 51"/52" or 6 1" Deck; Kit – ECO Plate 32" – 54" or 61"; Kit – Suspension Seat ZT200; Electric Deck Lift Kit ZT200; ZT Hitch Kit; BOSS-Vac PRO™ Collection System

Your Local Dealer Is:

Specifications while correct at the time of printing may change without notice.

BOB-CAT® is registered trade mark of Schiller Grounds Care, Inc.,

© 2009 Schiller Grounds Care, Inc. All Rights Reserved.,

One Bob Cat Lane, Johnson Creek WI 53038

www.bobcatturf.com • 920-699-2000



SCHILLER

GROUNDS CARE

JULY 2009