



BOB-CAT®

FAST CAT™

**Our Premium Professional
FastCat Mower offers
rugged features and
exceptional options to
deliver a superior cut
for all your turf needs.**

**It's just what
you need to
get more done
in less time!**



**Unbeatable Cutting Quality • Exceptional Traction
Superior Maneuverability • A Great Value!**

BOB-CAT® FastCat.

The little cat with the BIG Personality.

Specifications, while correct at the time of printing, may change without notice.

BOB-CAT® is a registered trademark of Commercial Grounds Care, Inc.

© 2008 CGC, Inc. • One BOB-CAT Lane • Johnson Creek, WI 53038 • www.bobcatturf.com

Your Local Dealer is:

BOB-CAT® FastCat

| MODELS | DECK SIZE | HORSEPOWER |
|-------------------------------|----------------|--------------|
| Kawasaki® KAI V-Twin | 36" Deck | 17 (12.7 kW) |
| Briggs & Stratton® Intek..... | 36" Deck | 21 (15.7 kW) |
| Kawasaki® KAI V-Twin | 42" Deck | 19 (14.2 kW) |
| Kawasaki® KAI V-Twin | 48" Deck | 19 (14.2 kW) |
| Kawasaki® KAI V-Twin | 52" Deck | 19 (14.2 kW) |

SPECIFICATIONS

Displacement

| | |
|-------------------------|--------------------------------|
| 17 hp..... | 585cc |
| 21 hp..... | 725cc |
| 19 hp | 585cc |
| 19 hp..... | 585cc |
| Engine Lubrication..... | Full Pressure – Spin-On Filter |

Deck Design

| | |
|-------------------------------|---|
| 36", 42" & 48" Decks | Fabricated 7-gauge top deck plus 7-gauge reinforcements – Reinforced Front Lip |
| 52" Deck..... | Fabricated – 2 layers of 10-gauge top deck plus 7-gauge reinforcements – Reinforced Front Lip |
| Deck Skirts | 7-gauge skirts |
| Cutter Spindle Type | Top Mounted 7" Diameter – 6 Bolt Maintenance Free w/1" Shaft & Split Steel Pulleys |
| Cutter Spindle Bearings | Double-Sealed, Precision Ground Ball Bearings |
| Cutting Height | 1.5" – 4.875" |
| Deck Lift Type | Manual with Quick-Lift Foot Assist |
| Deck Drive | 125 lb. ft. Warner Electric Clutch – Single Belt Drive |

Tractor Frame

| | |
|--------------------|--|
| Frame | Welded and Formed steel with tubular deck cradle |
| Transmission | Hydro-Gear ZT-2800 Commercial Duty Hydrostatic Drive Transaxle w/Variable Displacement Pumps |

Ground Speed

| | |
|---------------------|--|
| 36"..... | 7 mph forward – 3.5 mph reverse |
| 42", 48" & 52"..... | 8 mph forward – 3.5 mph reverse |
| Steering | Fully Dampened Twin Lever with Adjustable Controls |

Tires

| | |
|----------------------------------|--|
| Front Tires | 11 x 4.00-5 4-ply |
| Rear Tires: 36" | 18 x 6.50-12 |
| Rear Tires: 42", 48" & 52" | 20 x 8-10 |
| Parking Brake | Internal Integrated Wet Brake |
| Fuel Capacity | 8.5 Gallons (dual tanks) |
| Hourmeter | Digital – Standard |
| Seat | High-Back Adjustable with Armrests |
| Warranty | 2-year or 2,000 hours Commercial Machine Warranty, Engines covered by manufacturers' factory warranty. See dealer for details. |

Weight

| | |
|----------------|---------|
| 36", 42" | 785 lbs |
| 48", 52" | 825 lbs |

STANDARD FEATURES

Cup Holder, Storage Area, Polyester Based Powder Coat Paint, Yellow Dichromate Plating, Adjustable High-Back Seat with Armrests, 12 Volt DC Accessory Outlet, Sealed Maintenance Free Battery, Replaceable/Serviceable Front Caster Supports, Adjustable Control Levers, lift-off footplate

OPTIONS

Deluxe suspension seat, 3.75 or 5-Bushel Dump Grass Catcher, 2 Bag Spindle Driven BOSS-VAC™ Collection System, 2-post Roll Over Protection Structure (ROPS) with seat belt, 36", 48" or 52" Mulch Baffle Kit, 36" – 52" ECO Plate Kit, ZT Hitch Kit

Specifications, while correct at the time of printing, may change without notice.

BOB-CAT® is a registered trademark of Commercial Grounds Care, Inc.
© 2008 CGC, Inc. • One BOB-CAT Lane • Johnson Creek, WI 53038 • www.bobcatturf.com