



**BOB-CAT® HYDRO WALK-BEHIND MOWER
With Z-Control**



48" BOB-CAT® Hydro Walk Behind Mower with Z-Control.
Rugged, versatile hydraulic-drive walk-behind mowers.

BOB-CAT® HYDRO WALK-BEHIND MOWER with Z-Control

POWER

Engine17-HP (11.2 kW) 585cc Kawasaki KAI, V-twin, air-cooled, gas
Ignition Electronic with recoil start
Fuel Capacity 5 gal. (18.9 l) Polyethylene tank
Lubrication Pressure with filter
Air Cleaner Dual element

DRIVETRAIN

Transmission Hydrostatic drive with dual variable displacement pumps and wheel motors motor
Shaft Size 1 in. (25 mm) diameter tapered shaft
Drive Belt from engine to hydro input shafts; hydrostatic drive to wheels
Hydraulic Capacity 1.2 gal. (4.6 l) with 25-micron filtration
Brakes Hydrostat provides dynamic braking; dual-wheel parking brake
Drive Tires (2) 16 x 7.50-8 4-ply turf tread tubeless;
Caster Wheels:(2) 9 x 3.50-4 4-ply smooth tread with tube
Steering Fingertip levers at handles control independent power to each wheel for moving, stopping and power turning
Controls Throttle; speed selector/tracking levers; wheel drive Z-Control traction levers; blade drive switch; dual-wheel parking brake; operator-presence controls; keyed on/off switch (on/off/start switch on electric start models)
Speed (maximum) 6 mph (9.6 km/h) forward; 2 mph (3.2 km/h) reverse
Turning Radius True zero

DECKS

Fixed 48" Side Discharge Deck with Extreme Discharge System

DIMENSIONS

Overall Length 36" model77.6 in. (197 cm) Width
Transport Width (chute up)
48" Deck Model..... 48" (122 cm)

Weight

48"582 lbs. (264 kg)

ACCESSORIES

Jumbo grass catcher; 3.75 or 5 Bushel Fabric Dump Catcher; Eco plate kit; 36", 48" & 54" Mulch baffle kit with Eliminator Blades;
Hydro cold start Kit;

Specifications, while correct at time of printing, may change without notice.

Bob-Cat is a registered trademark of Commercial Grounds Care, Inc.

© 2008, CGC, Inc. One Bob Cat Lane, Johnson Creek, WI 53038

920-699-2000

www.bobcatturf.com

