



LIKE A **WALK**
IN THE PARK

FLOAT DECK HYDRO-DRIVE
WALK-BEHIND



MOW WITH
3 YEAR LIMITED
WARRANTY
CONFIDENCE

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

DRIVE AHEAD OF THE COMPETITION

The BOB-CAT® Float Deck Hydro Walk-Behind features a true float style DuraDeck™. Similar to the design of our zero-turn mower decks, it follows the contours of hilly and undulating terrain without scalping. The float deck is designed to move independently of the drive and caster wheels, allowing the deck to follow the contours of the ground. Single point height of cut adjustment easily raises and lowers the deck.

FEATURES:

- » Heavy-duty, durable electric clutch
- » Float deck models to help prevent scalping in uneven terrain
- » No-flat front caster wheels
- » Full pump and wheel motor design
- » Kawasaki® FX engines with heavy-duty air cleaners (on float deck models)
- » A reliable belt routing system to ensure long belt life and low maintenance costs
- » Intuitive controls to make every job easier to handle
- » 5-gallon fuel tank to keep you cutting longer



	Hydro Float Deck 936600	Hydro Float Deck 936601	Hydro Float Deck 936602		
ENGINE	Model	Kawasaki® FX541V	Kawasaki® FX600V	Kawasaki® FX651V	
	Displacement	603 cc	603 cc	726 cc	
	Lubrication	Full pressure - Spin on filter			
	Fuel Capacity	5 gal.			
	Air Filtration	Dual stage canister			
DECK	Mower Deck	DuraDeck™ side discharge with flexible molded polymer; Fabricated 7-gauge deck top plus 7-gauge reinforcements	DuraDeck™ side discharge with flexible molded polymer & Fabricated two-layer 10-gauge deck top	DuraDeck™ side discharge with flexible molded polymer & Fabricated two-layer 10-gauge deck top	
	Width	48"	52"	61"	
	Cutting Height	1.5" - 5.0"			
	Blade Tip Speed	18,600 fpm @ 3600 engine rpm	18,600 fpm @ 3600 engine rpm	18,600 fpm @ 3600 engine rpm	
	Deck Skirts	7-gauge skirts			
	Spindle Type	Maintenance-free with 1" shaft			
	Spindle Bearing	Double-sealed, precision ground ball bearings			
	Deck Drive	Warner Mag Stop 175 ft. lb. electric clutch			
	SIZE	Machine Length	80.7"	80.7"	81.3"
		Machine Height	40.3"	40.3"	40.3"
Machine Weight		780 lbs.	795 lbs.	860 lbs.	
TRANSMISSION	Type	Hydro-Gear variable displacement pumps			
	Pump Size	10 cc pumps with separate wheel motors			
	Ground Speed	6.7 mph	6.7 mph	6.7 mph	
WHEELS	Front Tires	11 x 4-5 no-flats			
	Rear Tires	18 x 7.5-8 4-ply			
	Drum	Hydrostatic dynamic braking - parking brake			
WARRANTY	3-year / 2500 hour Best in Industry MOW WITH CONFIDENCE™ Limited Warranty				

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

HUNT DOWN YOUR NEAREST BOB-CAT® DEALER AT BOBCATTURF.COM | 866-469-1242

