



**READY
TO TAME THE
TOUGHEST TURF**

Introducing the
XRZ™ Pro RS



MOW WITH
6 YEAR LIMITED
WARRANTY
CONFIDENCE

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

PROFESSIONAL, PERFORMANCE AND OUTSTANDING VALUE

The new BOB-CAT® XRZ™ Pro RS is our latest professional grade mower built for the lawn care contractor and the homeowner who wants to mow like one. Based on 60 years of engineering and manufacturing excellence, this latest edition to our zero-turn mower line comes packed with innovative new features. The XRZ™ Pro RS combines superior value with the toughness and reliability you've come to expect from a BOB-CAT®.

THE ALL-NEW XRZ™ PRO RS FEATURES:

- » TufDeck™ Pro 10-gauge fabricated, welded and reinforced steel mower deck
- » A choice of 48", 52" or 61" mowing decks
- » Patented Double-Wave™ Baffle System for maximum vacuum and lift
- » Powerful Kawasaki® FX series engines
- » HG ZT-3400 Twin Hydrostatic Transaxles for smooth performance and agility
- » High-back full mechanical suspension seat with armrests
- » Flip-up floor plate and open frame design
- » BOB-CAT® exclusive Zero-T 23" drive tires
- » 9.5-gallon fuel capacity
- » 6-year / 1200 hr MOW WITH CONFIDENCE™ Limited Warranty



		XRZ™ Pro RS 942630	XRZ™ Pro RS 942631	XRZ™ Pro RS 942632
ENGINE	Model	Kawasaki® FX651V	Kawasaki® FX691V	Kawasaki® FX730V
	Fuel Capacity	9.5 gal.	9.5 gal.	9.5 gal.
	Air Filtration	Dual stage canister	Dual stage canister	Dual stage canister
ELECTRICAL	Charging System	15 amp	15 amp	15 amp
	Clutch	125 ft. lb.	125 ft. lb.	125 ft. lb.
DECK	Mower Deck	TufDeck Pro	TufDeck Pro	TufDeck Pro
	Leading Edges	Adjustable front lip standard	Adjustable front lip standard	Adjustable front lip standard
	Width	48"	52"	61"
	Anti Scalp Rollers	3	3	7
	Cutting Height	1.5" - 4.875"	1.5" - 4.875"	1.5" - 4.875"
	Blade Tip Speed	17,365 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Extra Large Discharge Chute	Flexible molded polymer	Flexible molded polymer	Flexible molded polymer
FRAME	Form Welded	Welded 7-gauge steel 1.5 x 2.5" steel tubing 758 lbs.	Welded 7-gauge steel 1.5 x 2.5" steel tubing 774 lbs.	Welded 7-gauge steel 1.5 x 2.5" steel tubing 817 lbs.
	Machine weight			
TRANSMISSION	Type	Hydro-Gear® ZT-3400 Twin Hydrostatic Transaxles		
	Displacement	12 cc	12 cc	12 cc
	Oil Capacity	4 qts.	4 qts.	4 qts.
	Ground Speed	10 mph	10 mph	10 mph
WHEELS	Drive Wheel Size	23 x 10.5-12	23 x 10.5-12	23 x 10.5-12
	Front Caster Size	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6
	Caster Type	Pneumatic	Pneumatic	Pneumatic
SEAT	Description	Full Mechanical Suspension Seat	Full Mechanical Suspension Seat	Full Mechanical Suspension Seat
	Fore-Aft Adjustment	Seat slide lever	Seat slide lever	Seat slide lever
WARRANTY		6-year / 1200 hour MOW WITH CONFIDENCE™ Limited Warranty		

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

HUNT DOWN YOUR NEAREST BOB-CAT® DEALER AT BOBCATTURF.COM | 866-469-1242

