

# PROCAT™ 5000



MODEL NUMBER	9995010	9995011	9995012	9995008	9995009
<b>ENGINE</b>					
Model	B&S Vanguard 24hp	B&S Vanguard 24hp	B&S Vanguard 26hp	Kaw FX730V	Kaw FX801V
Displacement (cc)	724	810	810	726	852
Fuel Capacity (gal)	11	11	11	11	11
Air Filter	Canister Air Filter				
<b>ELECTRICAL</b>					
Charging System (amp)	15	15	15	15	15
Clutch (ft lb)	200	200	200	200	200
<b>DECK</b>					
Mower Deck	AirFX™ Cutting System				
Leading Edge	Adjustable, Front Lip Standard				
Width (in)	48	52	61	52	61
Adjustable Anti-Scalp Rollers	6	6	6	6	6
Cutting Height (in)	1–5.5	1–5.5	1–5.5	1–5.5	1–5.5
Blade Tip Speed	17800 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer				
<b>FRAME</b>					
Front & Rear	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing				
Machine Length (in)	83	83	83	83	83
Machine Weight—Wet (lb)	1253	1267	1318	1267	1318
<b>TRANSMISSION</b>					
Type	HG ZT-3400 Hydrostatic Transaxles				
Pump Displacement (cc)	12	12	12	12	12
Oil Capacity (qt)	2.5	2.5	2.5	2.5	2.5
Forward Speed (mph)	0–10	0–10	0–10	0–10	0–10
Reverse Speed (mph)	0–4	0–4	0–4	0–4	0–4
<b>WHEELS</b>					
Drive Wheel Size	24 x 8.5–12	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On	Bolt-On
<b>SEAT</b>					
Description	High-Back, Full-Mechanical Suspension Seat				
Fore-Aft Adjustment	Seat Slide Lever				
<b>WARRANTY</b> 6-year / 2,000 hour MOW WITH CONFIDENCE™ limited warranty					

**Parts & Accessories:** Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, BOSS-Vac™ 8-bushel, ZT Hitch Kit, No-Flat Caster Wheel Options, 61-inch Wide Track Kit, Magnetic Light Kit—12V, Striping Kit (48", 52", 61"), Light Kit—Footplate, Operator-Controlled Discharge Chute



## FIERCELY INDEPENDENT.

BOBCATTURF.COM