

QUICKCAT™ 4000



MODEL NUMBER	912360	912480	912520	912610
ENGINE				
Model	Kaw FX600V	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement (cc)	603	726	726	726
Fuel Capacity (gal)	5.1	6.5	6.5	6.5
Air Filter	Dual Element			
ELECTRICAL				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	125	200	200	200
DECK				
Mower Deck	DuraDeck™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	36	48	52	61
Adjustable Anti-Scalp Rollers	3	4	4	7
Cutting Height (in)	1.5–4.5	1.5–4.5	1.5–4.5	1.5–4.5
Blade Tip Speed	17600 fpm @ 3550 Engine rpm	17800 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
FRAME				
Front & Rear	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing			
Machine Length (in)	64	64	64	68
Machine Weight—Wet (lb)	800	961	991	1028
TRANSMISSION				
Type	HG ZT-3100 Hydrostatic Transaxles		HG ZT-3400 Hydrostatic Transaxles	
Pump Displacement (cc)	10	12	12	12
Oil Capacity (qt)	4	4	4	4
Forward Speed (mph)	0–9	0–10.5	0–10.5	0–10.5
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5	0–3.5
WHEELS				
Drive Wheel Size	20 x 8.0–10	23 x 8.5–12	23 x 10.5–12	23 x 10.5–12
Front Caster Wheel Size	11 x 4.0–5	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
SEAT				
Adjustment	Flip Up and Latch			
Rider Pad	Tethered, Removable for Service			
Vibration Isolation	Dampened			
WARRANTY	6-year / 2,000 hour MOW WITH CONFIDENCE™ limited warranty			

Parts & Accessories: Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, Hydro Cold-Start Kit (36", 48", 52"), No-Flat Caster Wheel Options, Magnetic Light Kit—12V, Operator-Controlled Discharge Chute



FIERCELY INDEPENDENT.

BOBCATTURF.COM