

# PREDATOR-PRO™ 7000



MODEL NUMBER	9997002	9997003	9997001	9997004
<b>ENGINE</b>				
Model	Kaw FX1000V	Kaw FX1000V	Kaw FX1000V	Kaw FX1000V
Displacement (cc)	999	999	999	999
Fuel Capacity (gal)	15	15	15	15
Air Filter	Canister Air Filter			
<b>ELECTRICAL</b>				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	250	250	250	250
<b>DECK</b>				
Mower Deck	AirFX™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	61	72	61	72
Adjustable Anti-Scalp Rollers	6	7	6	7
Cutting Height (in)	1–5.5	1–5.5	1–5.5	1–5.5
Blade Tip Speed	18500 fpm @ 3550 Engine rpm	18152 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm	18152 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
<b>FRAME</b>				
Front & Rear	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing			
Machine Length (in)	87	87	87	87
Machine Weight—Wet (lb)	1618	1659	1500	1541
<b>TRANSMISSION</b>				
Type	HG Pumps with HG Wheel Motors		HG ZT-5400 2-Speed Hydrostatic Transaxles	
Pump Displacement (cc)	16	16	16	16
Oil Capacity (qt)	9	9	5.9 each	5.9 each
Forward Speed (mph)	0–15	0–15	0–19*	0–19*
Reverse Speed (mph)	0–5	0–5	0–7.5**	0–7.5**
<b>WHEELS</b>				
Drive Wheel Size	26 x 12.0–12, 6-Spoke	26 x 12.0–12, 6-Spoke	26 x 12.0–12, 6-Spoke	26 x 12.0–12, 6-Spoke
Front Caster Wheel Size	15 x 6.5–6, No-Flat	15 x 6.5–6, No-Flat	15 x 6.5–6, No-Flat	15 x 6.5–6, No-Flat
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
<b>SEAT</b>				
Description	Extra-High Back, Full-Mechanical Suspension Seat			
Fore-Aft Adjustment	Seat Slide Lever			
<b>WARRANTY</b>	6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty			

\* 0–13 mph cutting; 13–19 mph transport

\*\* 0–5 mph cutting; 5–7.5 mph transport

**Parts & Accessories:** Mulching Baffle Kit – Eliminator Blades (61"), Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel (61"), BOSS-Vac™ Pro 12-bushel, BOSS-Vac™ 8-bushel (61"), 61-inch Wide Track Kit, Magnetic Light Kit—12V, Striping Kit, Operator-Controlled Discharge Chute



## FIERCELY INDEPENDENT.

BOBCATTURF.COM