

# XRZ™ PRO RS



MODEL NUMBER	942630	942631	942632	942633	942634
<b>ENGINE</b>					
Model	Kaw FX651V	Kaw FX691V	Kaw FX730V	Kaw FX850V	Kaw FX850V
Displacement (cc)	726	726	726	852	852
Fuel Capacity (gal)	9.5	9.5	9.5	9.5	9.5
Air Filter	Dual-Stage Canister				
<b>ELECTRICAL</b>					
Charging System (amp)	15	15	15	15	15
Clutch (ft lb)	125	125	125	200	200
<b>DECK</b>					
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts				
Leading Edge	Adjustable, Front Lip Standard				
Width (in)	48	52	61	52	61
Adjustable Anti-Scalp Rollers	3	3	7	3	7
Cutting Height (in)	1.5–4.875	1.5–4.875	1.5–4.875		
Blade Tip Speed	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer				
<b>FRAME</b>					
Front & Rear	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing				
Machine Length (in)	76	76	79	76	79
Machine Weight—Wet (lb)	773	789	832	TBD	TBD
<b>TRANSMISSION</b>					
Type	HG ZT-3400 Hydrostatic Transaxles				
Pump Displacement (cc)	12	12	12	12	12
Oil Capacity (qt)	4	4	4	4	4
Forward Speed (mph)	0–10	0–10	0–10	0–10	0–10
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5	0–3.5	0–3.5
<b>WHEELS</b>					
Drive Wheel Size	23 x 10.5–12	23 x 10.5–12	23 x 10.5–12	23 x 10.5–12	23 x 10.5–12
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Welded to Frame				
<b>SEAT</b>					
Description	High-Back, Full-Mechanical Suspension Seat				
Fore-Aft Adjustment	Seat Slide Lever				
<b>WARRANTY</b>					
6-year / 1,200 hour MOW WITH CONFIDENCE™ limited warranty					

Parts & Accessories: Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, ZT Hitch Kit, No-Flat Caster Wheel Options, Magnetic Light Kit—12V



## FIERCELY INDEPENDENT.

BOBATTURF.COM