

# XRZ™ PRO



MODEL NUMBER	942620	942621	942622
<b>ENGINE</b>			
Model	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement (cc)	726	726	726
Fuel Capacity (gal)	6	6	6
Air Filter	Dual Element		
<b>ELECTRICAL</b>			
Charging System (amp)	15	15	15
Clutch (ft lb)	125	125	125
<b>DECK</b>			
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts		
Leading Edge	Adjustable, Front Lip Standard		
Width (in)	48	52	61
Adjustable Anti-Scalp Rollers	3	3	7
Cutting Height (in)	1.5–4.875	1.5–4.875	1.5–4.875
Blade Tip Speed	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer		
<b>FRAME</b>			
Front & Rear	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing		
Machine Length (in)	76	76	79
Machine Weight—Wet (lb)	758	774	817
<b>TRANSMISSION</b>			
Type	HG ZT-3400 Hydrostatic Transaxles		
Pump Displacement (cc)	12	12	12
Oil Capacity (qt)	4	4	4
Forward Speed (mph)	0–8	0–8	0–8
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5
<b>WHEELS</b>			
Drive Wheel Size	22 x 11.0–10	22 x 11.0–10	22 x 11.0–10
Front Caster Wheel Size	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6
Caster Arm Attachment	Welded to Frame		
<b>SEAT</b>			
Description	High-Back, Spring Suspension Seat		
Fore-Aft Adjustment	Seat Slide Lever		
<b>WARRANTY</b>	6-year / 1,000 hour MOW WITH CONFIDENCE™ limited warranty		

Parts & Accessories: Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, ZT Hitch Kit, No-Flat Caster Wheel Options, Magnetic Light Kit—12V



## FIERCELY INDEPENDENT.

BOBCATTURF.COM