

# CRZ™



MODEL NUMBER	942607	942604	902605	902606
<b>ENGINE</b>				
Model	Kaw FR651V	Kaw FR651V	Kaw FR651V	Kaw FR691V
Displacement (cc)	726	726	726	726
Fuel Capacity (gal)	6	6	6	6
Air Filter	Dual Element			
<b>ELECTRICAL</b>				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	105	105	105	125
<b>DECK</b>				
Mower Deck	TufDeck™ 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts			
Leading Edge	Adjustable, 2 Positions			
Width (in)	42	48	52	61
Adjustable Anti-Scalp Rollers	2	3	3	7
Cutting Height (in)	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875
Blade Tip Speed	18809 fpm @ 3550 Engine rpm	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
<b>FRAME</b>				
Front & Rear	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing			
Machine Length (in)	82	80	80	80
Machine Weight—Wet (lb)	684	736	752	795
<b>TRANSMISSION</b>				
Type	HG ZT-2800 Hydrostatic Transaxles			
Pump Displacement (cc)	10	10	10	10
Oil Capacity (qt)	4	4	4	4
Forward Speed (mph)	0–7	0–7	0–7	0–7
Reverse Speed (mph)	0–3	0–3	0–3	0–3
<b>WHEELS</b>				
Drive Wheel Size	20 x 8.0–10	20 x 10.0–10	20 x 10.0–10	20 x 12.0–10
Front Caster Wheel Size	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6
Caster Arm Attachment	Welded to Frame			
<b>SEAT</b>				
Description	High-Back, Spring Suspension Seat			
Fore-Aft Adjustment	Seat Slide Lever			
<b>WARRANTY</b> 5-year / 500 hour MOW WITH CONFIDENCE™ limited warranty				

Parts & Accessories: Mulching Baffle Kit – Eliminator Blades (48", 52", 61"), Mulching Baffle Kit – Medium Lift Blades (42"), Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, No-Flat Caster Wheel Options, Magnetic Light Kit—12V



## FIERCELY INDEPENDENT.

BOBATTURF.COM